

Model TM-10

All the features of a high-end to<mark>aster... with a low-end price.</mark>

DAST TAY

The Hatco Toast-Max economy conveyor toaster offers the flexibility and performance to perfectly toast bread and buns fast – up to 300 slices per hour! Utilizing conveyor speed, not temperature, to determine toasting color, allows for instant adjustment of toasting time.

- 4-position toast selector switch: off / toast / buns / stand-by mode
- 89 mm (3½") clearance to accommodate high profile bread products
- Easy-to-load rack with front or rear discharging
- Permanently lubricated 50/60 Hz motor
- V-shaped reflectors help capture and redirect heat

- Long lasting serpentine metal sheathed heating elements
- 102 mm (4") adjustable legs
- Pilot light that signals unit is in operation
- Discharge and crumb trays are removable for easy cleaning






Nothing less than the best.™

CE







Models TM-5H, -10H

TM-5H Model

SPECIFICATIONS


| Model | kW | Туре | Cap./Min. [†] | Shipping Weight |
|--------|-----|--------------|------------------------|--------------------|
| TM-5H | 1.3 | Bread & Buns | 3 slices | 16 kg (36 lbs.) |
| TM-10H | 1.9 | Bread & Buns | 6 slices | 19 kg (41 lbs.) |

⁺ Toasting capacity may vary by product. Toasting of coated products is not recommended.

SELECTOR CHART

(Based on serving 2 slices per customer.)


| Number of Customers | Serving Time TM-5H | Serving Time TM-10H | |
|------------------------|-----------------------|------------------------|--|
| 30 | 24 minutes | 12 minutes | |
| 60 | 48 minutes | 24 minutes | |
| 90 | 72 minutes | 36 minutes | |
| 120 | 96 minutes | 48 minutes | |



PRODUCT SPECS Conveyor Toaster

The electric Conveyor Toaster shall be a Hatco Modelas manufactured by the Hatco Corporation, Milwaukee, WI 53234 U.S.A.

The toaster shall have the capacity to toast up to pieces per minute and it shall be rated atkW,volts, single phase.



TM-10H Model

DIMENSIONS

TOAST-MAX "CONVEYOR TOASTERS

TM-5H: 289 W x 416 D x 387 H mm

(11³/8" W x 16³/8" D x 15¹/4" H).

TM-10H: 368 W x 416 D x 387 H mm (14¹/2" W x 16³/8" D x 15¹/4" H).

Interior Cavity Openings:

TM-5H: 187 Ŵ x 89 mm H (7³/8" W X 3 ¹/2" H). TM-10H: 264 W x 89 mm H (10 ³/8" W X 3 ¹/2" H).

Maximum Product Size:

245 W x 64 mm H (9⁵/8" W x 2¹/2"H).

CORD LOCATION

Left side of back of unit near center.

PLUG CONFIGURATIONS

| F₽ | |
|---------|----------------|
| BS-1363 | CEE 7/7 Schuko |

ELECTRIC RATING

| Model | Volts | Watts | Amps | Hz |
|--------|---------|-----------|---------|-------|
| TM-5H | 220-240 | 1340-1595 | 6.1-6.6 | 50-60 |
| TM-10H | 220-240 | 1940-2300 | 8.8-9.6 | 50-60 |

The toaster shall be made of stainless steel design and shall include a front mounted control panel with variable speed control, 4-position toast selector switch and a toast collector pan.

The toaster will have metal sheathed heating elements.

HATCO CORPORATION P.O. Box 340500 Milwaukee, WI 53234-0500 U.S.A. • (414) 671-6350 • Fax (414) 671-3976 Web Site: www.hatcocorp.com • E-mail: intlsales@hatcocorp.com

-33